

**Product Description**  
**MASON Self Drilling Screw Hex “High”**

**Supplier**  
**Fasten Enterprises Pte Ltd**

**Product Specifications**

- Brand name** : **MASON**
- Screw diameter** : **M5 / #10 gauge**
- Thread form** : **16 threads per inch**
- Screw head drive** : **5/16” (8mm) Hex Drive**
- Drill capacity** : **Up to 3.5mm thickness (#2 point)**
- Material** : **Case Hardened Carbon Steel**
- Protective Coating** : **Zinc Plated**



**M5 - 16 X 16MM HEX “HIGH” (ZINC PLATED)**  
**Product Code: MAS-501616HH-ZC**

Thickness of Steel Material	Tensile Pullout Resistance
1.2 mm	1.70 kN
1.6 mm	2.40 kN
2.3 mm	4.00 kN
3.2 mm	6.80 kN
4.2 mm	-
6.0 mm	-

Tensile Resistance	13.80kN
Shear Resistance	9.00kN
Torque Resistance	11.36Nm

**FASTEN ENTERPRISES PTE LTD**

ADDRESS : 3 Ang Mo Kio Street 62, #01-50/51, Singapore 569139  
 EMAIL : office@fasten.com.sg WEBSITE : www.fasten.com.sg  
 GST REG. No.: M2-0035840-6 CO REG No.: 197902740K

PHONE : +65 6741 2998  
 FAX : +65 6741 7606

