

Product Description
MASON Self Drilling Screw Hex RP

Supplier
Fasten Enterprises Pte Ltd

Product Specifications

- Brand name** : **MASON**
- Screw diameter** : **M6.3 / #14 gauge**
- Thread form** : **14 threads per inch**
- Screw head drive** : **3/8" (10mm) Hex Drive**
- Drill capacity** : **<2.5mm thickness (Reduced Point)**
- Material** : **Case Hardened Carbon Steel**
- Protective Coating** : **Ruspert Silver AS3566 Class 3**



M6.3 – 14 X 22MM HEX RP (RUSPERT SILVER)
Product Code: MAS-631422HRP-RS

Thickness of Steel Material	Tensile Pullout Resistance
1.2 mm	-
1.6 mm	-
2.3 mm	4.40 kN
3.2 mm	-
4.2 mm	-
6.0 mm	-

Tensile Resistance	20.80 kN
Shear Resistance	14.60 kN
Torque Resistance	21.98Nm

FASTEN ENTERPRISES PTE LTD

ADDRESS : 3 Ang Mo Kio Street 62, #01-50/51, Singapore 569139
 EMAIL : office@fasten.com.sg WEBSITE : www.fasten.com.sg
 GST REG. No.: M2-0035840-6 CO REG No.: 197902740K

PHONE : +65 6741 2998
 FAX : +65 6741 7606

